

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

CHEMWATCH 5051-68
Version No:7.1.1.1
Page 1 of 11

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Wattyl Cold Galvanising Aerosol

PROPER SHIPPING NAME

AEROSOLS

PRODUCT USE

Used according to manufacturer's directions.
Application is by spray atomisation from a hand held aerosol pack.

SUPPLIER

Company: Valspar Australia Pty Ltd Pty Limited
Address:
Level 4, 2 Burbank Place
Baulkham Hills
NSW, 2153
Australia
Telephone: +61 2 8867 3333
Emergency Tel: **+61 1800 039 008**
Emergency Tel: **+61 3 9573 3112**
Fax: +61 2 8867 3344

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

RISK

Risk Codes	Risk Phrases
R12	• Extremely flammable.
R20/21/22	• Harmful by inhalation, in contact with skin and if swallowed.
R36/38	• Irritating to eyes and skin.
R44	• Risk of explosion if heated under confinement.
R48/20	• Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53	• Very toxic to aquatic organisms, may cause long- term adverse effects in the aquatic environment.
R63(3)	• Possible risk of harm to the unborn child.
R67	• Vapours may cause drowsiness and dizziness.
R33?	• Cumulative effects may result following exposure*.
R37?	• May produce discomfort of the respiratory system*.
R40(3)?	• Limited evidence of a carcinogenic effect*.
R66?	• Repeated exposure potentially causes skin dryness and cracking*.

SAFETY

Safety Codes	Safety Phrases
S16	• Keep away from sources of ignition. No smoking.
S23	• Do not breathe gas/fumes/vapour/spray.
S24	• Avoid contact with skin.
S25	• Avoid contact with eyes.
S36	• Wear suitable protective clothing.
S37	• Wear suitable gloves.
S39	• Wear eye/face protection.
S51	• Use only in well ventilated areas.
S09	• Keep container in a well ventilated place.
S53	• Avoid exposure - obtain special instructions before use.
S29	• Do not empty into drains.

continued...

Wattyl Cold Galvanising Aerosol

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

Hazard Alert Code: **EXTREME**

CHEMWATCH 5051-68

Version No:7.1.1.1

Page 2 of 11

Section 2 - HAZARDS IDENTIFICATION

S401	<ul style="list-style-type: none">To clean the floor and all objects contaminated by this material, use water and detergent.
S07	<ul style="list-style-type: none">Keep container tightly closed.
S35	<ul style="list-style-type: none">This material and its container must be disposed of in a safe way.
S13	<ul style="list-style-type: none">Keep away from food, drink and animal feeding stuffs.
S26	<ul style="list-style-type: none">In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	<ul style="list-style-type: none">If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S57	<ul style="list-style-type: none">Use appropriate container to avoid environmental contamination.
S61	<ul style="list-style-type: none">Avoid release to the environment. Refer to special instructions/Safety data sheets.
S60	<ul style="list-style-type: none">This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
mineral turpentine	Not avail.	10-30
aromatic solvent 100	Not avail.	10-30
zinc powder	7440-66-6	10-30
epoxy ester resin, unregulated		5-15
xylene	1330-20-7	1-9
aluminium powder coated additives, unregulated	7429-90-5	1-5
propellant as dimethyl ether	115-10-6	10-30
contains less than 0.1% benzene		

Section 4 - FIRST AID MEASURES

SWALLOWED

- Not considered a normal route of entry.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.

EYE

- If aerosols come in contact with the eyes:
- Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If solids or aerosol mists are deposited upon the skin:
- Flush skin and hair with running water (and soap if available).
- Remove any adhering solids with industrial skin cleansing cream.
- DO NOT use solvents.
- Seek medical attention in the event of irritation.

INHALED

- If aerosols, fumes or combustion products are inhaled:
- Remove to fresh air.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.

continued...

Wattyl Cold Galvanising Aerosol

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

Hazard Alert Code: **EXTREME**

CHEMWATCH 5051-68

Version No:7.1.1.1

Page 3 of 11

Section 4 - FIRST AID MEASURES

- If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

Treat symptomatically.

- Absorption of zinc compounds occurs in the small intestine.
- The metal is heavily protein bound.
- Elimination results primarily from faecal excretion.
- The usual measures for decontamination (Ipecac Syrup, lavage, charcoal or cathartics) may be administered, although patients usually have sufficient vomiting not to require them.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

■ SMALL FIRE:

- Water spray, dry chemical or CO₂

LARGE FIRE:

- Water spray or fog.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

2YE

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.

continued...

Wattyl Cold Galvanising Aerosol

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

Hazard Alert Code: EXTREME

CHEMWATCH 5051-68

Version No:7.1.1.1

Page 4 of 11

Section 6 - ACCIDENTAL RELEASE MEASURES

- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- Reacts violently with caustic soda, other alkalis - generating heat, highly flammable hydrogen gas.
- If alkali is dry, heat generated may ignite hydrogen - if alkali is in solution may cause violent foaming.
- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
Australia Exposure Standards	xylene (Xylene (o-, m-, p- isomers))	80		150	655				
Australia Exposure Standards	dimethyl ether (Dimethyl ether)	400		500	950				

The following materials had no OELs on our records

- zinc powder:

CAS:7440- 66- 6

ODOUR SAFETY FACTOR (OSF)

OSF=0.042 (mineral turpentine)

- Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

continued...

Wattyl Cold Galvanising Aerosol

Hazard Alert Code: **EXTREME**

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

CHEMWATCH 5051-68
Version No:7.1.1.1
Page 5 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

MATERIAL DATA

AROMATIC SOLVENT 100:

MINERAL TURPENTINE:

XYLENE:

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

DIMETHYL ETHER:

ZINC POWDER:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

AROMATIC SOLVENT 100:

MINERAL TURPENTINE:

Odour threshold: 0.25 ppm.

The TLV-TWA is protective against ocular and upper respiratory tract irritation and is recommended for bulk handling of gasoline based on calculations of hydrocarbon content of gasoline vapour.

AROMATIC SOLVENT 100:

MINERAL TURPENTINE:

For trimethyl benzene as mixed isomers (of unstated proportions)

Odour Threshold Value: 2.4 ppm (detection)

Use care in interpreting effects as a single isomer or other isomer mix. Trimethylbenzene is an eye, nose and respiratory irritant.

MINERAL TURPENTINE:

for benzene

Odour Threshold Value: 34 ppm (detection), 97 ppm (recognition)

NOTE: Detector tubes for benzene, measuring in excess of 0.5 ppm, are commercially available. The relative quality of epidemiological data and quantitative health risk assessments related to documented and theoretical leukaemic deaths constitute the basis of the TLV-recommendation.

For white spirit:

Low and high odour thresholds of 5.25 and 157.5 mg/m³, respectively, were considered to provide a rather useful index of odour as a warning property.

The TLV-TWA is calculated from data on the toxicities of the major ingredients and is intended to minimise the potential for irritative and narcotic effects, polyneuropathy and kidney damage produced by vapours.

for ethyl benzene:

Odour Threshold Value: 0.46-0.60 ppm

NOTE: Detector tubes for ethylbenzene, measuring in excess of 30 ppm, are commercially available.

Ethyl benzene produces irritation of the skin and mucous membranes and appears to produce acute and chronic effects on the central nervous system.

CEL TWA: 80 ppm, 480 mg/m³ [Shell]

AROMATIC SOLVENT 100:

For cumene:

Odour Threshold Value: 0.008-0.132 ppm (detection), 0.047 ppm (recognition)

Exposure at or below the TLV-TWA is thought to prevent induction of narcosis.

CEL TWA: 50 ppm, 250 mg/m³ as total hydrocarbons [Manufacturer]

continued...

Wattyl Cold Galvanising Aerosol

Hazard Alert Code: **EXTREME**

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

CHEMWATCH 5051-68
Version No:7.1.1.1
Page 6 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ZINC POWDER:

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience).

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

XYLENE:

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

ALUMINIUM POWDER COATED:

For aluminium oxide and pyrophoric grades of aluminium:

Twenty seven year experience with aluminium oxide dust (particle size 96% 1,2 um) without adverse effects either systemically or on the lung, and at a calculated concentration equivalent to 2 mg/m³ over an 8-hour shift has lead to the current recommendation of the TLV-TWA.

The limit should also apply to aluminium pyro powders whose toxicity is reportedly greater than aluminium dusts and should be protective against lung changes.

For aluminium oxide:

The experimental and clinical data indicate that aluminium oxide acts as an "inert" material when inhaled and seems to have little effect on the lungs nor does it produce significant organic disease or toxic effects when exposures are kept under reasonable control.

[Documentation of the Threshold Limit Values], ACGIH, Sixth Edition.

DIMETHYL ETHER:

for dimethyl ether:

The no-effect-level for dimethyl ether is somewhere between 2000 ppm (rabbits) and 50,000 ppm (humans) with possible cardiac sensitisation occurring around 200,000 ppm (dogs). The AIHA has adopted a safety factor of 100 in respect to the 50,000 ppm level in its recommendation for a workplace environmental exposure level (WEEL) which is thought to protect against both narcotic and sensitising effects.

May act as a simple asphyxiants; these are gases which, when present in high concentrations, reduce the oxygen content in air below that required to support breathing, consciousness and life; loss of consciousness, with death by suffocation may rapidly occur in an oxygen deficient atmosphere.

CARE: Most simple asphyxiants are odourless or possess low odour and there is no warning on entry into an oxygen deficient atmosphere.

PERSONAL PROTECTION

RESPIRATOR

• Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

■ No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- Safety glasses with side shields.
- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

HANDS/FEET

- No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.

OTHER

■ No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

continued...

Wattyl Cold Galvanising Aerosol

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

Hazard Alert Code: **EXTREME**

CHEMWATCH 5051-68
Version No:7.1.1.1
Page 7 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Supplied as an aerosol pack. Contents under PRESSURE.

Grey highly flammable liquid with a solvent odour; not miscible with water.

PHYSICAL PROPERTIES

Liquid.

Gas.

Does not mix with water.

Sinks in water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	- 41 propellant	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	350 propellant	Vapour Pressure (kPa)	UNDER PRESSURE
Upper Explosive Limit (%)	26.7 propellant	Specific Gravity (water=1)	1.63- 1.68
Lower Explosive Limit (%)	3.5 propellant	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	60- 65	Evaporation Rate	Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Not normally a hazard due to physical form of product.

Accidental ingestion of the material may be damaging to the health of the individual.

Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions. Damage to the heart muscle can produce heart beat irregularities, ventricular fibrillation (fatal) and ECG changes. The central nervous system can be depressed. Light species can cause a sharp tingling of the tongue and cause loss of sensation there. Aspiration can cause cough, gagging, pneumonia with swelling and bleeding.

Ingestion of alkyl ethers may produce stupor, blurred vision, headache, dizziness and irritation of the nose and throat.

Respiratory distress and asphyxia may result.

Considered an unlikely route of entry in commercial/industrial environments.

continued...

Wattyl Cold Galvanising Aerosol

Hazard Alert Code: **EXTREME**

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

CHEMWATCH 5051-68

Version No:7.1.1.1

Page 8 of 11

Section 11 - TOXICOLOGICAL INFORMATION

EYE

■ There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with redness. There may be damage to the cornea. Unless treatment is prompt and adequate there may be permanent loss of vision. Conjunctivitis can occur following repeated exposure.

Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.

Eye contact with alkyl ethers (vapour or liquid) may produce irritation, redness and tears.

SKIN

■ The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time.

Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Spray mist may produce discomfort.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Toxic effects may result from skin absorption.

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

INHALED

■ Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour displace and replace air in breathing zone, acting as a simple asphyxiant.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

CHRONIC HEALTH EFFECTS

■ Principal route of occupational exposure to the gas is by inhalation.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Metallic dusts generated by the industrial process give rise to a number of potential health problems. The larger particles, above 5 micron, are nose and throat irritants. Smaller particles however, may cause lung deterioration. Particles of less than 1.5 micron can be trapped in the lungs and, dependent on the nature of the particle, may give rise to further serious health consequences.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

CARCINOGEN

xylene	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans
--------	--	-------	---	---

SKIN

xylene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
xylene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1

Section 12 - ECOLOGICAL INFORMATION

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

continued...

Watty Cold Galvanising Aerosol

Hazard Alert Code: EXTREME

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

CHEMWATCH 5051-68
Version No:7.1.1.1
Page 9 of 11

Section 12 - ECOLOGICAL INFORMATION

Refer to special instructions/ safety data sheets.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
mineral turpentine	No Data Available	No Data Available	No Data Available	No Data Available
aromatic solvent 100	No Data Available	No Data Available	No Data Available	No Data Available
zinc powder	No Data Available	No Data Available	LOW	No Data Available
xylene	LOW	LOW	LOW	No Data Available
aluminium powder coated	No Data Available	No Data Available	No Data Available	No Data Available
dimethyl ether	LOW	No Data Available	LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE GAS

HAZCHEM:
 2YE (ADG7)

ADG7:

Class or Division	2.1	Subsidiary Risk1:	None
UN No.:	1950	Packing Group:	None
Special Provision:	63 190 277 327	Limited Quantity:	See SP 277
Portable Tanks & Bulk Containers - Instruction:	None	Portable Tanks & Bulk Containers - Special Provision:	None
Packagings & IBCs - Packing Instruction:	P003 LP02	Packagings & IBCs - Special Packing Provision:	PP17 PP87 L2
Name and Description: AEROSOLS			

Air Transport IATA:

ICAO/IATA Class	2.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1950	Packing Group:	-
Special provisions:	A145A167A802		
Cargo Only			
Packing Instructions: Passenger and Cargo	203	Maximum Qty/Pack: Passenger and Cargo	150 kg
Packing Instructions: Passenger and Cargo Limited Quantity	203	Maximum Qty/Pack: Passenger and Cargo Limited Quantity	75 kg
Packing Instructions:	Y203	Maximum Qty/Pack:	30 kg G

Shipping name:AEROSOLS

Maritime Transport IMDG:

IMDG Class	2.1	IMDG Subrisk:	None
UN Number:	1950	Packing Group:	None
EMS Number:	F-D,S-U	Special provisions:	63 190 277 327 344 959
Limited Quantities:	SP277	Marine Pollutant:	Yes
Shipping name:AEROSOLS			

continued...

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

CHEMWATCH 5051-68

Version No:7.1.1.1

Page 10 of 11

Section 14 - TRANSPORTATION INFORMATION

Section 15 - REGULATORY INFORMATION

Indications of Danger:

F+ Extremely flammable
N Dangerous for the environment
Xn Harmful

POISONS SCHEDULE

None

REGULATIONS

Regulations for ingredients

zinc powder (CAS: 7440-66-6) is found on the following regulatory lists;

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (AQUA/1 to 6 - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (IRRIG - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (STOCK - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (IRRIG)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (STOCK)", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Environment Protection (Ambient Air Quality) Measure - Schedule 1: Pollutants", "Australia National Environment Protection (Ambient Air Quality) Measure - Schedule 2 Table 1: Standards and Goal for Pollutants other than Particles as PM2.5", "Australia National Pollutant Inventory", "FisherTransport Information", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments", "WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established"

xylene (CAS: 1330-20-7) is found on the following regulatory lists;

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

aluminium powder coated (CAS: 7429-90-5) is found on the following regulatory lists;

"Acros Transport Information", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (AQUA/1 to 6 - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (IRRIG - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (STOCK - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause

continued...

Wattyl Cold Galvanising Aerosol

Chemwatch Material Safety Data Sheet
Issue Date: 23-Sep-2013
X9317SP

Hazard Alert Code: **EXTREME**

CHEMWATCH 5051-68

Version No:7.1.1.1

Page 11 of 11

Section 15 - REGULATORY INFORMATION

environmental harm - Domestic water supply quality", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (IRRIG)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (STOCK)", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Environment Protection (Ambient Air Quality) Measure - Schedule 1: Pollutants", "Australia National Environment Protection (Ambient Air Quality) Measure - Schedule 2 Table 1: Standards and Goal for Pollutants other than Particles as PM2.5", "Australia National Pollutant Inventory", "International Numbering System for Food Additives", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information", "WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established"

dimethyl ether (CAS: 115-10-6, 157621-61-9) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information"

No data for Wattyl Cold Galvanising Aerosol (CW: 5051-68)

No data for mineral turpentine (CAS: , Not avail)

No data for aromatic solvent 100 (CAS: , Not avail)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
dimethyl ether	115-10-6, 157621-61-9

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 23-Sep-2013

Print Date: 10-Mar-2015

This is the end of the MSDS.