

Chemwatch Material Safety Data Sheet  
Issue Date: 17-Sep-2013  
X9317SP

CHEMWATCH 24-5418  
Version No:3.1.1.1  
Page 1 of 10

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

Wattyl Colourthane NS300 Pt B

### PROPER SHIPPING NAME

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

### PRODUCT USE

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

### SUPPLIER

Company: Valspar Australia Pty Ltd Pty Limited

Address:

Level 4, 2 Burbank Place

Baulkham Hills

NSW, 2153

Australia

Telephone: +61 2 8867 3333

Emergency Tel: **+61 1800 039 008**

Emergency Tel: **+61 3 9573 3112**

Fax: +61 2 8867 3344

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.**

### RISK

Risk Codes

R11

R20

R37/38

R41

R52/53

R65

R67

R21/22?

R33?

R61?

R66?

Risk Phrases

- Highly flammable.
- Harmful by inhalation.
- Irritating to respiratory system and skin.
- Risk of serious damage to eyes.
- Harmful to aquatic organisms, may cause long- term adverse effects in the aquatic environment.
- HARMFUL- May cause lung damage if swallowed.
- Vapours may cause drowsiness and dizziness.
- Skin contact and/or ingestion may produce health damage\*.
- Cumulative effects may result following exposure\*.
- May be harmful to the foetus/ embryo\*.
- Repeated exposure potentially causes skin dryness and cracking\*.

### SAFETY

Safety Codes

S16

S23

S24

S25

S36

S37

S39

S51

S09

S53

S29

S401

Safety Phrases

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin.
- Avoid contact with eyes.
- Wear suitable protective clothing.
- Wear suitable gloves.
- Wear eye/face protection.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- Avoid exposure - obtain special instructions before use.
- Do not empty into drains.
- To clean the floor and all objects contaminated by this material, use water

continued...

## Chemwatch Material Safety Data Sheet

Issue Date: 17-Sep-2013

X9317SP

CHEMWATCH 24-5418

Version No:3.1.1.1

Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

S07	and detergent.
S13	• Keep container tightly closed.
S13	• Keep away from food, drink and animal feeding stuffs.
S26	• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	• If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S60	• This material and its container must be disposed of as hazardous waste.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
resin		10-30
solvents		40-70
n- butanol	71-36-3	10-30

## Section 4 - FIRST AID MEASURES

**SWALLOWED**

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.

**EYE**

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.

**SKIN**

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

**INHALED**

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

**NOTES TO PHYSICIAN**

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

To treat poisoning by the higher aliphatic alcohols (up to C7):

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.

For acute or short term repeated exposures to xylene:

- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.

continued...

- Pulmonary absorption is rapid with about 60-65% retained at rest.
- Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> < 50 mm Hg or pCO<sub>2</sub> > 50 mm Hg) should be intubated.

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

- Water spray or fog.
  - Alcohol stable foam.
  - Dry chemical powder.
  - Carbon dioxide.
- Do not use a water jet to fight fire.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water course.

### FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
  - Severe fire hazard when exposed to heat, flame and/or oxidisers.
  - Vapour may travel a considerable distance to source of ignition.
  - Heating may cause expansion or decomposition leading to violent rupture of containers.
- Combustion products include: carbon dioxide (CO<sub>2</sub>), formaldehyde, other pyrolysis products typical of burning organic material.  
 Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

### FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

### HAZCHEM

•3YE

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

### MAJOR SPILLS

Chemical Class: alcohols and glycols

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
--------------	------	-------------	------------	-------------

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

## Section 7 - HANDLING AND STORAGE

**PROCEDURE FOR HANDLING**

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.

Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers.
- Vent periodically
- Always release caps or seals slowly to ensure slow dissipation of vapours.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec).
- Avoid splash filling.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

**SUITABLE CONTAINER**

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.

**STORAGE INCOMPATIBILITY**

- Avoid reaction with oxidising agents.

**STORAGE REQUIREMENTS**

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**EXPOSURE CONTROLS**

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
Australia Exposure Standards	Wattyl Colourthane NS300 Pt B (Xylene (o-, m-, p- isomers))	80		150	655				
Australia Exposure Standards	n- butanol (n- Butyl alcohol)	50							

**MATERIAL DATA**

N-BUTANOL:

WATTYL COLOURTHANE NS300 PT B:

For n-butanol:

Odour Threshold Value: 0.12-3.4 ppm (detection), 1.0-3.5 ppm (recognition)

NOTE: Detector tubes for n-butanol, measuring in excess of 5 ppm are commercially available.

continued...

# Wattyl Colourthane NS300 Pt B

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 17-Sep-2013

X9317SP

CHEMWATCH 24-5418

Version No:3.1.1.1

Page 5 of 10

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure at or below the TLV-TWA is thought to provide protection against hearing loss due to vestibular and auditory nerve damage in younger workers and to protect against the significant risk of headache and irritation.

25 ppm may produce mild irritation of the respiratory tract 50 ppm may produce headache and vertigo.

Higher concentrations may produce marked irritation, sore throat, coughing, nausea, shortness of breath, pulmonary injury and central nervous system depression characterised by headache, dizziness, dullness and drowsiness.

### WATTYL COLOURTHANE NS300 PT B:

for diacetone alcohol:

Odour Threshold Value: 0.27 ppm (detection), 1.1 ppm (recognition)

The TLV-TWA is thought to be protective against eye, nose and throat irritation. Eye irritation appeared in the majority of subjects exposed for 15 minutes to 100 ppm.

Odour Threshold Value: 3.6 ppm (detection), 699 ppm (recognition)

Saturation vapour concentration: 237000 ppm @ 20 C

NOTE: Detector tubes measuring in excess of 40 ppm, are available.

Exposure at or below the recommended TLV-TWA is thought to protect the worker against mild irritation associated with brief exposures and the bioaccumulation, chronic irritation of the respiratory tract and headaches associated with long-term acetone exposures.

for propylene glycol monomethyl ether acetate (PGMEA)

Saturated vapour concentration: 4868 ppm at 20 C.

A two-week inhalation study found nasal effects to the nasal mucosa in animals at concentrations up to 3000 ppm.

for ethyl benzene:

Odour Threshold Value: 0.46-0.60 ppm

NOTE: Detector tubes for ethylbenzene, measuring in excess of 30 ppm, are commercially available.

Ethyl benzene produces irritation of the skin and mucous membranes and appears to produce acute and chronic effects on the central nervous system.

for methyl isobutyl ketone (MIBK):

Unfatigued, odour recognition threshold (100% test panel) is 0.3 - 0.5 ppm.

Distinct odour at 15 ppm.

Odour is objectionable and vapours are irritating to eyes at 200 ppm.

NOTE: Detector tubes for methyl isobutyl ketone, measuring in excess of 50 ppm, are commercially available.

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

### N-BUTANOL:

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

## PERSONAL PROTECTION

continued...

# Wattyl Colourthane NS300 Pt B

Hazard Alert Code: HIGH

## Chemwatch Material Safety Data Sheet

Issue Date: 17-Sep-2013

X9317SP

CHEMWATCH 24-5418

Version No:3.1.1.1

Page 6 of 10

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### RESPIRATOR

• Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

### HANDS/FEET

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

### OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

### ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Clear colourless to pale yellow liquid with a solvent odour; not miscible with water.

### PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	<23	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	<1
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

continued...

**Section 10 - STABILITY AND REACTIVITY****CONDITIONS CONTRIBUTING TO INSTABILITY**

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

*For incompatible materials - refer to Section 7 - Handling and Storage.*

**Section 11 - TOXICOLOGICAL INFORMATION****POTENTIAL HEALTH EFFECTS****ACUTE HEALTH EFFECTS****SWALLOWED**

- Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

Accidental ingestion of the material may be damaging to the health of the individual.

**EYE**

- If applied to the eyes, this material causes severe eye damage.

**SKIN**

- This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Open cuts, abraded or irritated skin should not be exposed to this material.

**INHALED**

- Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

The acute toxicity of inhaled alkylbenzenes is best described by central nervous system depression. As a rule, these compounds may also act as general anaesthetics.

Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow. Nausea and vomiting are seen, and liver and kidney damage is possible as well following massive exposures. Symptoms are more acute the more carbons there are in the alcohol.

Inhalation hazard is increased at higher temperatures.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

**CHRONIC HEALTH EFFECTS**

- Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Some glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous. Higher concentrations and prolonged exposure can cause blood in the urine.

**TOXICITY AND IRRITATION**

- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

for propylene glycol ethers (PGEs):

Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB);

# Wattyl Colourthane NS300 Pt B

Hazard Alert Code: HIGH

## Chemwatch Material Safety Data Sheet

Issue Date: 17-Sep-2013

X9317SP

CHEMWATCH 24-5418

Version No:3.1.1.1

Page 8 of 10

## Section 11 - TOXICOLOGICAL INFORMATION

dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM).

Testing of a wide variety of propylene glycol ethers Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series.

A BASF report (in ECETOC ) showed that inhalation exposure to 545 ppm PGMEA (beta isomer) was associated with a teratogenic response in rabbits; but exposure to 145 ppm and 36 ppm had no adverse effects.

The beta isomer of PGMEA comprises only 10% of the commercial material, the remaining 90% is alpha isomer.

### CARCINOGEN

n- butanol	Australia Exposure Standards	Carcinogen Category	Sk
------------	------------------------------	---------------------	----

### SKIN

n- butanol	Australia Exposure Standards - Skin	Notes	Sk
n- butanol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2

## Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

### Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
n- butanol	LOW	MED	LOW	HIGH

## Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

## Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

### HAZCHEM:

•3YE (ADG7)

### ADG7:

Class or Division:	3	Subsidiary Risk1:	None
UN No.:	1263	Packing Group:	II
Special Provision:	163 *	Limited Quantity:	5 L
Portable Tanks & Bulk Containers - Instruction:	T4	Portable Tanks & Bulk Containers - Special	TP1 TP8 TP28

continued...



# Wattyl Colourthane NS300 Pt B

Hazard Alert Code: HIGH

## Chemwatch Material Safety Data Sheet

Issue Date: 17-Sep-2013

X9317SP

CHEMWATCH 24-5418

Version No:3.1.1.1

Page 9 of 10

## Section 14 - TRANSPORTATION INFORMATION

Packagings & IBCs - Packing Instruction:	P001 IBC02	Provision: Packagings & IBCs - Special Packing Provision:	PP1
Name and Description: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant [AUST.] entries)			
<b>Air Transport IATA:</b>			
ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	II
Special provisions:	A3A72		
Cargo Only			
Packing Instructions: Passenger and Cargo	364	Maximum Qty/Pack: Passenger and Cargo	60 L
Packing Instructions: Passenger and Cargo Limited Quantity	353	Maximum Qty/Pack: Passenger and Cargo Limited Quantity	5 L
Packing Instructions:	Y341	Maximum Qty/Pack:	1 L

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

### Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	II
EMS Number:	F-E,S-E	Special provisions:	163
Limited Quantities:	5 L		

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

## Section 15 - REGULATORY INFORMATION

### Indications of Danger:

F Highly Flammable  
Xn Harmful

### POISONS SCHEDULE

S5

### REGULATIONS

#### Wattyl Colourthane NS300 Pt B (CAS: ) is found on the following regulatory lists;

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "OECD List of High Production Volume (HPV) Chemicals", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

#### Regulations for ingredients

#### n-butanol (CAS: 71-36-3) is found on the following regulatory lists;

"Acros Transport Information", "Australia Exposure Standards", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code

continued...

Chemwatch Material Safety Data Sheet

Issue Date: 17-Sep-2013

X9317SP

CHEMWATCH 24-5418

Version No:3.1.1.1

Page 10 of 10

Section 15 - REGULATORY INFORMATION

Chapter 17: Summary of minimum requirements", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "Sigma-AldrichTransport Information"

**ethylbenzene (CAS: 100-41-4) is found on the following regulatory lists;**

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (AQUA/1 to 6 - non-pesticide anthropogenic organics)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "Sigma-AldrichTransport Information", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

### Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 17-Sep-2013

Print Date: 11-Sep-2015

*This is the end of the MSDS.*