



DESCRIPTION

- a single pack, clear, water based polyurethane coating for interior timber floors

PRINCIPAL CHARACTERISTICS

- water based, low odour, non-flammable
- quick drying, allowing 3 coat application in 1 day
- easy clean up
- non yellowing formulation
- suitable for domestic and commercial interior timber, parquetry and cork floors

Note: We advise that you test this product to determine if it is suitable for your particular use.

COLOUR AND GLOSS

- clear, full gloss

BASIC DATA AT 25° C and 50% RELATIVE HUMIDITY

- touch dry..... 30 minutes (longer in cold or adverse drying conditions)
- dry to sand..... 2 hours
- recoat 3 hours
- walk on..... 24 hours (light traffic)
- fully cured 3 days
- practical spreading rate 10 m²/L, depending on the porosity of the substrate
- clean up..... wash brushes and equipment with water
- shelf life (cool, dry place) at least 12 months in unopened container

SURFACE PREPARATION

New Timber:

- ensure timber is dry, free from dirt, grease and wax
- fill nail holes or cracks with WattyI Woodstop Timber Putty in a matching colour (do not use linseed oil putty). Allow to dry for at least 30 minutes, then fine-sand using equipment and paper appropriate to the flooring material
- do not over-sand

Surfaces previously coated with WattyI Instant Estapol, Estapol 7008 or Estapol SP Gloss:

- sand surface with coarse sandpaper until no gloss remains
- aged floors can exhibit timber movement, bruising and floor cupping: these create difficulties in sanding the floor sufficiently well to ensure satisfactory adhesion of the recoat film
- it is advisable to mechanically-sand the floor

Surfaces previously coated with a water-based clear finish:

- wash surface with a 1% detergent solution in water, and sand lightly
- vacuum floor thoroughly to remove all dust before coating
- if required, stain with WattyI Floor Stain (11692-LINE). Direct staining with dye-based stains is not recommended



ESTAPOL[®] WATER BASED GLOSS TM11.40

INSTRUCTIONS FOR USE

- agitate thoroughly with a flat-bladed stirrer before and during use
- if required, thin first coat up to 5% with water, do not thin subsequent coats
- may be applied by brush, applicator pad, or Wattyl applicator pad
- do not apply by spray or roller
- apply evenly over the surface, finishing with strokes along the grain. If using a paint pad to apply the finish, use a "moving puddle" techniques, i.e. pour a quantity of finish on to the floor and use the paint pad to move the coating outwards until the floor has a smooth, even coating; finish along the grain, and do not overspread the coating
- do not apply excessively heavy coats
- allow to dry for at least three hours (longer in cold or adverse conditions) before applying a second coat
- sand lightly (using 240grit sandpaper) and vacuum the surface between the first and second coats to remove any raised grain
- do not sand between subsequent coats
- apply a minimum of three coats
- for recommendations outside those contained in this data sheet, refer to Wattyl

SAFETY PRECAUTIONS

- avoid contact with skin and eyes
- use gloves, mask and goggles during application
- provide adequate ventilation when using in confined spaces
- this product is intended for use in industrial situations by professional applicators in accordance with the advice given on this sheet. All work involving the use and application of this product should be carried out in compliance with all relevant Health, Safety & Environmental standards and regulations and must not be used without reference to the Material Safety Data Sheet (MSDS)

PACKAGING

20 litres

(smaller pack sizes available in the retail range)

For the most up to date information contact Wattyl Customer Service Hotline or visit the Wattyl Website.

CUSTOMER SERVICE HOTLINE	Australia 132 101	New Zealand 0800 735 551
WEBSITE	http://www.wattyl.com.au	http://www.wattyl.co.nz

Wattyl and Estapol are registered trademarks of Wattyl Australia Pty Ltd.

1. This information is important to ensure that the listed Wattyl product(s) perform according to the stated application and uses and must be followed to meet Wattyl's warranties express and implied. Wattyl advises that you (a) review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) ensure that the product be used only in accordance with the information provided by Wattyl and the product(s) be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (c) thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl does not warrant that the information provided is current when the product is used or is wholly comprehensive. 3. For all product and non-product related information, Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl office before using the product(s). 4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product. If coating rectification is required Wattyl Technical Services shall be contacted prior to commencement. WATTYL AUSTRALIA PTY LTD (ABN 40 000 035 914)